

Upper Temperature Range: 2°C to 8°C  
Lower Temperature Range: -10°C to -25°C

## Combo Refrigerator



### Standard Equipment

- Double wall PUF insulation
- Interior SS304 & Exterior PPGI
- Stainless Steel Trays in the upper compartment & Baskets in the lower compartment
- Doors with magnetic gasket for all airtight sealing
- Forced air circulation for uniform temperature
- PU Wheels for easy movement
- CFC free cooling system consisting of hermetically sealed compressor coupled with evaporation coil & condenser (one for each compartment)
- Complete operation are driven through IOT-enabled Controller with data logging capacity of upto 1000 readings
- High speed Ethernet based communication
- All operations through a single 7" Color Touch Screen Display
- High-quality PT-100 Temperature sensor
- Safety devices: Low Temperature cut-off settable thermostats
- Audio/Visual alarms for deviations
- Complete with DQ, IQ, OQ, PQ ,SOP & Operational Manual

**Power Supply:** 230 volts 50 Hz main supply. Also available with 60 Hz Cycle.

## Double the Output | Lower the Cost

### SPECIFICATIONS

- Upper Temperature Range : 2°C to 8°C
- Lower Temperature Range : -10°C to -25°C
- Upper Temperature Accuracy :  $\pm 0.5^{\circ}\text{C}$
- Lower Temperature Accuracy :  $\pm 3^{\circ}\text{C}$
- Upper Temperature Uniformity :  $\pm 1^{\circ}\text{C}$
- Lower Temperature Uniformity :  $\pm 5^{\circ}\text{C}$

### Optional Accessories

- ICDAS -A Single Software installation for all Newtronic make equipments
- Remote alarm system suitable for upto 4 nos. Newtronic make equipments
- Mobile Alert System

### ◆ Selection Guide

Model	Capacity		Internal Size (H*W*D) mm	External Size (H*W*D) mm	Trays/ Baskets Qty.
	CuFt.	Liter			
NLCR17MIC	Upper - 7	Upper - 300	Upper - 765 x 625 x 630	2050 x 785 x 945	Upper - 3
	Lower - 7	Lower - 165	Lower - 440 x 625 x 600		Lower - 2

\* Newtronic reserve the rights to change the product specifications without prior notice.

### Features

