

Upper Temperature Range: 2°C to 8°C
 Lower Temperature Range: -10°C to -25°C

Combo Refrigerator



Standard Equipment

- Double wall PUF insulation
- Interior SS 304 & Exterior Mild Steel
- Stainless Steel Trays
- Doors with magnetic gasket for all airtight sealing
- Forced air circulation for uniform temperature
- PU Wheels for easy movement
- CFC free cooling system consisting of hermetically sealed compressor coupled with evaporation coil & condenser
- Complete operation are driven through IOT-enabled Controller with data logging capacity of upto 1000 readings
- High speed Ethernet based communication
- All operations through a single 7" Color Touch Screen Display
- High-quality PT-100 Temperature sensor
- Safety devices: Low Temperature cut-off settable thermostats
- Audio/Visual alarms for deviations
- Complete with DQ, IQ, OQ, PQ ,SOP & Maintenance Manual

Power supply: 230 volts 50 Hz main supply. Also available with 60 Hz Cycle.

SPECIFICATIONS

- Upper Temperature Range: 2°C to 8°C
- Lower Temperature Range: -10°C to -25°C

Optional Accessories

- ICDAS -A Single Software installation for all Newtronic make equipments
- Remote alarm system suitable for upto 4 nos. Newtronic make equipments
- Mobile Alert System

◆ Selection Guide

Model	Capacity		Internal Size (H*W*D) mm	External Size (H*W*D) mm	Trays Qty.	Trays Size (W*D) mm	Approx. Weight (Kg)	
	CuFt.	Liter					Equip.	Ship.
NLCR14MI	Upper - 7	Upper - 200	Upper - 510 X 560 X 700	2070 X 720 X 1005	Upper - 2	540 X 605	300	375
	Lower - 7	Lower - 200	Lower - 510 X 560 X 700		Lower - 2			

* Newtronic reserve the rights to change the product specifications without prior notice.

Features	Ethernet	Alarms	Mobile Alert	Safety	Software	Documents