

Temperature Range: (Ambient+5)°C to 60°C

# Laboratory (Bacteriological) Incubators

## Standard Equipment

- Double walled with PUF insulation
- SS 304 Interior & Exterior either SS 304 or Mild Steel
- Stainless Steel trays
- Forced air circulation for uniform temperature
- PU wheels for easy movement
- SS tubular heaters
- Complete operations driven through PID controller with data logging capacity of upto 1000 readings and with online print facility
- High speed Ethernet based communication
- High-quality PT-100 Temperature sensor
- Safety devices: High temperature cut-off settable thermostats
- Audio/Visual alarms for deviations
- Complete with DQ, IQ, OQ, PQ ,SOP & Maintenance Manual



**Power supply:** 230 volts 50 Hz main supply. Also available with 60 Hz Cycle.

## SPECIFICATIONS

- Temperature Range : (Ambient+5)°C to 60°C

## Optional Accessories

- ICDAS -A Single Software installation for all Newtronic make equipments
- Remote alarm system suitable for upto 4 nos. Newtronic make equipments
- Mobile Alert System

## ◆ Selection Guide

Model	Capacity		Internal Size (H*W*D) mm	External Size (H*W*D) mm	Trays Qty.	Trays Size (W*D) mm
	CuFt.	Liter				
NLLO3SE	3	90	450 X 450 X 450	800 X 560 X 760	2	430 X 430
NLLO5SE	5	121	600 X 450 X 450	950 X 560 X 820	2	430 X 430
NLLO8SE	8	216	600 X 600 X 600	950 X 760 X 1030	2	560 X 560
NLLO12SE	12	324	900 X 600 X 600	1410 X 760 X 1060	3	560 X 560
NLLO16SE	16	430	1200 X 600 X 600	1710 X 760 X 1125	4	560 X 560
NLLO26SE	26	735	1500 X 700 X 700	2010 X 860 X 1225	5	660 X 660
NLLO34SE	34	1000	1500 X 800 X 800	2010 X 960 X 1325	5	760 X 760

\* Newtronic reserve the rights to change the product specifications without prior notice.

